



備註:

1. 材質: PM-9820
2. 強度要求: 1.50kg MIN
3. 耐壓要求: 4KV/1.5mA/60S
4. 焊錫溫度: $450^\circ \pm 10^\circ$ 3SEC
5. 拉力: 焊後拉力 2.5kg MIN
6. 模具狀況: 量產模
7. 尺寸公差

A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R
33.00	33.00	16.70	15.10	PL	44.80	0.80	5.90	7.50	4.10	10.80	20.40	12.80	27.30	39.00	8.80	16.40	
$+0.1$ -0.2	$+0.1$ -0.2	± 0.3	$+0.1$ -0.05	± 0.2	± 0.25	± 0.05	± 0.1	± 0.1	$+0.1$ -0.2	$+0.1$ -0.2	± 0.3	± 0.2	± 0.2	± 0.3	± 0.2	± 0.3	

客户确认
签回

RoHS
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	UQ-4013 (4P)	MATERIAL	PM-9820	SCALE	1:1	ANGLE	$\pm 1^\circ$
DRAWING NO.	HX-4023	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	00
东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com				TOLERANCE OF PIN DIA ± 0.05			
				PIN TENSION LOAD kg MIN		UL REC. :94V0	
DRAWN & DRAFTED BY		LIN HUA JING		CHECKED & APPROVED BY		DATE: DEC 25 2015	