



備註說明:

1. 材質: PM-9823
2. 強度要求: 1.50kg MIN
3. 耐壓要求: 4KV/1.5mA/1分鐘
4. 焊錫溫度: 450° ±10° 3SEC
5. 焊錫前拉力: 1.00kg MIN
焊錫後拉力: 2.00kg MIN
6. 模具狀況: 量產模

A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S
10.70	17.60	11.40	9.70	7.10	5.10	26.00	13.60	8.60		2.50	12.60	7.40	6.50	8.00	9.95	0.50	12.80	3.20
±0.2	±0.3	±0.2	±0.2	+0.1/-0.15	±0.15	±0.3	±0.2	±0.15		±0.15	±0.2	±0.15	±0.1	±0.1	±0.15	±0.05	±0.15	±0.15

客户确认
签回

RoHS
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	ATQ-17(10P)	MATERIAL	PM-9823	SCALE	1:1	ANGLE	±1°
DRAWING NO.	HX-1713	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	00
东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO.,LTD. TEL:0769-86388088 86388188 86388288 FAX:0769-86388111 http://www.hxbobbin.com E-Mail:hxbobbin@vip.163.com		TOLERANCE OF PIN DIA ±0.05				UL REC. :94V0	
		TOLERANCE:0<L<4:±0.1 4<L<16:±0.2 16<L<63:±0.3					
DRAWN & DRAFTED BY		LIN HUA JING		CHECKED & APPROVED BY		DATE: OCT 09 2019	