



- 備註說明:
1. 材質: PM-9630
  2. 強度要求: 1.50kg MIN
  3. 耐壓要求: 4KV/1.5mA/1分鐘
  4. 焊錫溫度: 450° ±10° 3SEC
  5. 焊前拉力: 1.0kg Min, 焊後拉力: 1.5kg MIN
  6. PIN切面100%鍍錫, 不可氧化
  7. 模具狀況: 量產模

客户确认	RoHS HF
签回	

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	ATQ-17 (5P)	MATERIAL	PM-9630	SCALE	1:1	ANGLE	±1°
DRAWING NO.	HX-1716	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	00
		TOLERANCE OF PIN DIA ±0.05				UL REC. :94V0	
东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL:0769-86388088 86388188 86388288 FAX:0769-86388111 http://www.hxbobbin.com E-Mail:hxbobbin@vip.163.com		TOLERANCE: 0<L≤4: ±0.1 4<L≤16: ±0.2 16<L≤63: ±0.3		DRAWN & DRAFTED BY		DATE: OCT 08 2018	
		LIN HUA JING		CHECKED & APPROVED BY			