



A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T
16.00	13.90	7.60	6.10	8.60	3.81	2.00	6.10	18.60	18.20	14.10	12.40		15.00	0.60	6.10	7.80	22.00	18.20	21.20
±0.2	±0.15	±0.2	±0.1	±0.2	±0.1	±0.1	±0.1	±0.3	±0.3	±0.15	±0.2		±0.2	±0.05	±0.1	±0.2	±0.3	±0.3	±0.3

客户确认
签回

RoHS
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01	1. E, G, I尺寸由7.50, 2.30, 17.50改为8.60, 2.00, 18.60	2012/12/14	03	1. K, N, Q尺寸由13.70, 15.24, 7.60改为14.10, 15.00, 7.80	2016/06/23
02	1. O尺寸由0.80改为0.60	2013/05/20	04	BASE線槽深度由3.50mm改為3.00mm	2018/04/09

NAME	EF-20 (10P)	MATERIAL	T375HF	SCALE	2:1	ANGLE	±1°
DRAWING NO.	HX-2009	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	04
东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com		TOLERANCE OF PIN DIA ±0.05					
		PIN TENSION LOAD 1.0 kg MIN		UL REC. :94V0			
		TOLERANCE: 0<L<4: ±0.1 4<L<16: ±0.2 16<L<63: ±0.3					
DRAWN & DRAFTED BY		LIN HUA JING		CHECKED & APPROVED BY		DATE: DEC 14 2012	