



NOTE:

1. 材质: PM9823 (UL94V-0, UL No. E41429)
2. 颜色: 黑色
3. 铁芯型号: EF-20
4. PIN材质: CP WIRE, 1H  $\phi 0.70 \pm 0.05\text{mm}$
5. 需符合超越《环境关联物质管理规范》
6. 毛边最大为0.05mm
7. BOBBIN底部平面度 $\leq 0.1\text{mm}$
8. PIN拉力要求: 焊前1.0kg MIN; 焊后1.5kg MIN.
9. 最小壁厚0.41mm.
10. 尺寸公差带

$0 < L \leq 1 \quad \pm 0.06$   
 $1 < L \leq 4 \quad \pm 0.10$   
 $4 < L \leq 16 \quad \pm 0.15$   
 $16 < L \leq 63 \quad \pm 0.20$   
 $63 < L \leq 250 \quad \pm 0.30$   
 ANGULAR DIMS  $\pm 1/2 \text{ DEG}$

客户确认  
 签回

RoHS  
 HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	EF-20 (13P)	MATERIAL	PM-9823	SCALE	1:1	ANGLE	$\pm 1^\circ$
DRAWING NO.	HX 2066	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	00
东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com		TOLERANCE OF PIN DIA $\pm 0.05$				TOLERANCE:	
		PIN TENSION LOAD kg MIN		UL REC. : 94V0			
DRAWN & DRAFTED BY		LIN PENG FEI		CHECKED & APPROVED BY		LIN HUA JING	
				DATE:		JUN 11 2025	