



備註說明:

1. 材質: PF-2736
2. 強度要求: 1.50kg MIN
3. 耐壓要求: 4KV/1.5mA/1分鐘
4. 焊錫溫度: 450° ±10° 3SEC
5. 拉力: 焊後拉力 1.5kg MIN
6. 模具狀況: 样品模

A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	客户确认	RoHS HF
14.80 ±0.2	13.20 ±0.2	5.20 ±0.2	23.50 ±0.2	0.60 ±0.05	14.70 ±0.2	9.20 +0.2 -0	11.30 ±0.2	4.00 ±0.1	1.50 ±0.1	3.15 ±0.1	20.50 ±0.3	10.40 ±0.2	20.50 ±0.3	3.70 ±0.1	PL ±0.2	签回	
REV.	REVISION RECORD					DATE	REV	REVISION RECORD					DATE				
01							03										
02							04										

NAME	EFD-2020 (10P)	MATERIAL	PF-2736	SCALE	1:1	ANGLE	±1°
DRAWING NO.	HX 2042	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	00
东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO.,LTD. TEL:0769-86388088 86388188 86388288 FAX:0769-86388111 http://www.hxbobbin.com E-Mail:hxbobbin@vip.163.com		TOLERANCE OF PIN DIA ±0.05		—⊕—			
		PIN TENSION LOAD 1.0 kg MIN		UL REC. :94V0			
TOLERANCE: 0<L<4: ±0.1 4<L<16: ±0.2 16<L<63: ±0.3				DRAWN & DRAFTED BY LIN HUA JING			
CHECKED & APPROVED BY				DATE: JUN 28 2016			