



注意防呆點不是PIN 1

備註說明:

1. PART NO. : HX-2211 量產模
2. MATERIAL: T375HF MUST MEET UL94V-0
3. COLOR: BLACK
4. CORE TYPE: EFD-2222
5. MATERIAL OF PIN : 3/4H CP WIRE, SQ0.64±0.05
6. DIMENSION MARK :  $\triangle$  MAIN DIM.,  $\otimes$  SECOND DIM., OTHER WIRE ARE REFERENTIAL DIM.
7. 強度要求: 1.80kg MIN
8. 耐壓要求: 4KV/1.5mA/1分鐘
9. 焊錫溫度: 450° ±10° 3SEC
10. 拉力: 焊後拉力 1.53kg MIN

标示的  $\triangle$  为重要尺寸, 标示的  $\otimes$  为次要尺寸。

A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R
15.60	10.20	8.60	5.60	12.60	4.30	16.00	13.60	7.40	0.64	19.00	1.70	2.30	21.40	22.50			
±0.2	±0.2	+0.1/-0	+0.1/-0	±0.2	±0.2	+0.05/-0.2	±0.2	±0.2	±0.05	±0.2	±0.1	±0.1	±0.3	±0.3			

客户确认  
签回

RoHS  
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01	$\triangle$ 防呆點高度由0.80mm改為1.10mm	2016/08/16	03		
02	$\triangle$ D尺寸由5.60+0.1/-0改為5.70±0.05	2022/03/30	04		

NAME	EFD-2222 (10P)	MATERIAL	T375HF	SCALE	1:1	ANGLE	±1°
DRAWING NO.	HX-2211	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	02



东莞市华欣塑胶制品有限公司  
DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD.  
TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111  
http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com

TOLERANCE OF PIN DIA	±0.05	
PIN TENSION LOAD	1.5 kg MIN	UL REC. : 94V0
TOLERANCE:	0<L<4: ±0.1    4<L<16: ±0.2    16<L<63: ±0.3	
DRAWN & DRAFTED BY	LIN HUA JING	CHECKED & APPROVED BY
DATE:	JAN 18 2014	