



備註說明:

1. MATERIAL: T375HF MUST MEET UL94V-0
2. COLOR: BLACK
3. CORE TYPE: EL-19
4. 強度要求: 2.00kg MIN
5. 耐壓要求: 4KV/1.5mA/1分鐘
6. 焊錫後拉力: 1.50kg MIN
7. 模具狀況: 量產模
8. PIN來回90°折彎一次無折斷、龜裂

A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S
13.90	7.30	7.00	3.90	19.50	30.00	16.50	7.30	5.50	4.50	PL	6.80	13.00	0.70	21.60	6.00	5.50	20.30	16.70
±0.2	±0.2	±0.2	±0.1	±0.3	±0.3	±0.3	±0.2	±0.2	±0.2	±0.2	±0.2	±0.15	±0.05	±0.3	±0.2	±0.2	±0.3	±0.3

客户确认  
 簽回

RoHS  
 HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	EL-19 (10P)	MATERIAL	T375HF	SCALE	2:1	ANGLE	±1°
DRAWING NO.	HX 1902	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	00



东莞市华欣塑胶制品有限公司  
 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD.  
 TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111  
 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com

TOLERANCE OF PIN DIA	±0.05	
PIN TENSION LOAD	1.2 kg MIN	UL REC. :94V0
TOLERANCE:	0<L≤4: ±0.1    4<L≤16: ±0.2    16<L≤63: ±0.3	
DRAWN & DRAFTED BY	LIN HUA JING	CHECKED & APPROVED BY
DATE:	APR 29 2004	