



備註 (NOTE):

1. 拉力: 焊前1.3kg MIN; 焊後2.0kg MIN
2. BASE擋板葉片平貼度0.10mm MAX
3. 尺寸公差:

0<L≤1	±0.06
1<L≤4	±0.10
4<L≤16	±0.15
16<L≤63	±0.20
63<L≤250	±0.30
ANGULAR DIMS ± 1/2 DEG	

客户确认
签回

RoHS
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	PQ-20 (14P)	MATERIAL	PM-9820	SCALE	1:1	ANGLE	±1°
DRAWING NO.	HX 2064	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	00



东莞市华欣塑胶制品有限公司
DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD.
TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111
http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com

TOLERANCE OF PIN DIA ±0.02		— ⊕ —	
PIN TENSION LOAD 1.3 kg MIN		UL REC. : 94V0	
TOLERANCE:			
DRAWN & DRAFTED BY	LIN PENG FEI	CHECKED & APPROVED BY	LIN HUA JING
DATE:		APR 06 2025	