



備註說明:

1. 模具狀況: 正式模。
2. 此BASE與HX-2029B輪軸匹配OK。
3. 材質T375HF
4. 強度: 1.0KG MIN
5. 耐壓: 4KV/1.5mA/1MIN
6. 焊錫溫度: 450+/-10°C 3SEC
7. 焊錫前拉力: 1.0KG MIN
焊錫後拉力: 1.5KG MIN

客户确认
签回

RoHS
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01	△防呆凸點尺寸由0.7*0.6改為1.1*0.9	2023/09/21	03		
02			04		

NAME	SQ-2020 (4P)	MATERIAL	T375HF	SCALE	1/1	ANGLE	±1°	
DRAWING NO.	HX 2029A	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	01	
 东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com		TOLERANCE OF PIN DIA ±0.05				PIN TENSION LOAD 1.5 kg MIN		UL REC. :94V0
		TOLERANCE: 0<L<4: ±0.1 4<L<16: ±0.2 16<L<63: ±0.3		DRAWN & DRAFTED BY		LIN HUA JING	CHECKED & APPROVED BY	