



備註說明:

1. 材質: PET-FR530
2. 強度要求: 1.50kg MIN不脆斷
3. 耐壓要求: 4KV/1.5mA/1分鐘
4. 模具狀況: 量產模

A	B	C	D	E	F	G	H	I	J	K	L
11.20	1.90	14.00	6.20	7.80	1.80	4.50	4.40	4.50	1.80	12.00	17.00
$\pm 0.2$	$\pm 0.1$	$+0.1 / -0.2$	$+0.3 / -0.1$	$\pm 0.2$	$\pm 0.1$	$\pm 0.15$	$\pm 0.2$	$\pm 0.2$	$\pm 0.1$	$\pm 0.2$	$\pm 0.2$



REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
A			C		
B			D		

NAME	SQ-2022	MATERIAL	PET-FR530	SCALE	1:1	ANGLE	$\pm 1^\circ$
DRAWING NO.	HX 2052	PIN MATERIAL		UNIT	m/m	REV.	00
		PIN TENSION LOAD      kg MIN      UL REC. :94V0		TOLERANCE: $0 < L < 4: \pm 0.1$ $4 < L < 16: \pm 0.2$ $16 < L < 63: \pm 0.3$			
东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO.,LTD. TEL:0769-86388088 86388188 86388288 FAX:0769-86388111 http://www.hxbobbin.com E-Mail:hxbobbin@vip.163.com	DRAWN & DRAFTED BY LIN HUA JING	CHECKED & APPROVED BY LIN GUO PING	DATE: OCT 07 2017				