



備註說明:

1. 材質: T375HF
2. 強度要求: 1.50kg MIN
3. 耐壓要求: 4KV/1.5mA/1分鐘
4. 焊錫溫度: 450° ±10° 3SEC
5. 拉力: 焊後拉力 1.5kg MIN
6. 模具狀況: 正式模

A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R
18.40	16.00	11.60	9.60	13.00	12.80	16.50	14.20	11.50	8.00	PL	10.00	5.20	0.80	13.60	21.00	8.50	16.30
±0.3	+0.3 -0.2	±0.2	±0.2	±0.2	±0.2	±0.3	±0.2	±0.2	±0.2	±0.2	±0.2	±0.2	±0.05	±0.2	±0.3	±0.2	±0.3

客户确认
签回

RoHS
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01	增加標示凸點高度尺寸	2016/09/22	03		
02			04		

NAME	UT-20 (4P)	MATERIAL	T375HF	SCALE	2:1	ANGLE	±1°
DRAWING NO.	HX 2001	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	01
 东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO.,LTD. TEL:0769-86388088 86388188 86388288 FAX:0769-86388111 http://www.hxbobbin.com E-Mail:hxbobbin@vip.163.com		TOLERANCE OF PIN DIA ±0.05					
		PIN TENSION LOAD 1.5 kg MIN		UL REC. :94V0			
		TOLERANCE: 0<L<4: ±0.1 4<L<16: ±0.2 16<L<63: ±0.3					
DRAWN & DRAFTED BY		LIN HUA JING		CHECKED & APPROVED BY		DATE: MAY 30 2006	