



(进胶口位置)

(红色线条是合模线位置)

備註說明:

1. 材質: PBT-4130
2. 強度要求: 1.50kg MIN, 中間葉片 1.0kg MIN
3. 耐壓要求: 4KV/0.5mA/3S
4. 焊錫溫度:
5. 与HX-2001, HX-2007匹配OK
6. 模具狀況: 量產模

RoHS

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
A	I, B, C, F, K, M尺寸由0.50, 3.20, 11.30, 14.00, 6.20改为0.70, 3.00, 11.50, 13.90, 6.15(mm)	2009/09/06	C		
B			D		

NAME	UT-20	MATERIAL	PBT-4130	SCALE	2:1	ANGLE	±1°
DRAWING NO.	HX-2002	PIN MATERIAL		UNIT	m/m	REV.	01
<p>东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com</p>		TOLERANCE OF PIN PITCH ±0.20				UL REC. :94V0	
		TOLERANCE: 0<L≤4: ±0.1 4<L≤16: ±0.2 16<L≤63: ±0.3				DRAWN & DRAFTED BY LIN HUA JING	
		DATE: AUG 28 2009					