


正齿轮 M=1 10T



O. D=12

P. D=10



備註說明:

1. 兩輪軸組配後鐵芯孔尺寸為6.25±0.2mm。



RoHS

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
A	1. B, E, H, J, K尺寸由0.80, 3.20, 11.30, 14.00, 6.20改为0.75, 3.00, 11.50, 13.90, 6.15(mm)	2009/09/06	C		
B	1. K尺寸由6.15改为6.25 (mm)	2012/07/26	D		

NAME	UT-20	MATERIAL	PET-FR530	SCALE	2/1	ANGLE	±1°
DRAWING NO.	HX 2003	PIN MATERIAL		UNIT	m/m	REV.	02
 东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com		PIN TENSION LOAD		kg MIN	UL REC. :94V0		
		TOLERANCE: 0<L≤4: ±0.1 4<L≤16: ±0.2 16<L≤63: ±0.3					
DRAWN & DRAFTED BY		LIN HUA JING	CHECKED & APPROVED BY		LIN GUO PING	DATE:	JUL 26 2012