



備註說明:

1. 材質: T375HF
2. 強度要求: 凸點1.50kg MIN, 其他位置3.0kg MIN
3. 耐壓要求: 4KV/1.5mA/1分鐘
4. 焊錫溫度: 450° ±10° 3SEC
5. 拉力: 焊後拉力 1.5kg MIN
6. 模具狀況: 正式模

紅色線條是合模線位置

| | | | | | | | | | | | | | | | | | |
|-------|-----------|-------|-------|-------|-------|-------|-------|-------|------|------|-------|------|-------|-------|-------|------|-------|
| A | B | C | D | E | F | G | H | I | J | K | L | M | N | O | P | Q | R |
| 18.40 | 16.00 | 11.60 | 10.80 | 13.00 | 13.80 | 17.80 | 14.20 | 11.50 | 8.20 | PL | 10.00 | 5.20 | 0.80 | 13.60 | 21.00 | 8.50 | 16.30 |
| ±0.3 | +0.3/-0.2 | ±0.2 | ±0.2 | ±0.15 | ±0.2 | ±0.3 | ±0.2 | ±0.2 | ±0.2 | ±0.2 | ±0.15 | ±0.2 | ±0.05 | ±0.2 | ±0.3 | ±0.2 | ±0.3 |

客户确认
签回

RoHS
HF

| | | | | | |
|------|-----------------|------|-----|-----------------|------|
| REV. | REVISION RECORD | DATE | REV | REVISION RECORD | DATE |
| 01 | | | 03 | | |
| 02 | | | 04 | | |

| | | | | | | | |
|--|------------|---|---------|-----------------------|-----|-----------------------------|-----|
| NAME | UT-20 (4P) | MATERIAL | T375HF | SCALE | 2:1 | ANGLE | ±1° |
| DRAWING NO. | HX-2038 | PIN MATERIAL | CP WIRE | UNIT | m/m | REV. | 00 |
| 东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com | | TOLERANCE OF PIN DIA ±0.05 | | | | PIN TENSION LOAD 1.5 kg MIN | |
| | | TOLERANCE: 0<L<4: ±0.1 4<L<16: ±0.2 16<L<63: ±0.3 | | UL REC. :94V0 | | DATE: MAR 19 2015 | |
| DRAWN & DRAFTED BY | | LIN HUA JING | | CHECKED & APPROVED BY | | | |