







進膠口位置



植PIN深度



備註說明:

1. 材質: PM-9823
2. 強度要求: 1.20kg MIN
3. 耐壓要求: 4KV/1.5mA/1分鐘
4. 焊錫溫度: 450° ±10° 3SEC
5. 焊錫前拉力: 1.00kg MIN
焊錫後拉力: 1.50kg MIN
6. 模具狀況: 量產模

客户确认
签回

RoHS
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	ATQ-2311 (5+2P)	MATERIAL	PM-9823	SCALE	1:1	ANGLE	±1°	
DRAWING NO.	HX-2317A	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	01	
<p>东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com</p>		TOLERANCE OF PIN DIA ±0.05				PIN TENSION LOAD kg MIN		UL REC. :94V0
		TOLERANCE: 0<L≤4: ±0.1 4<L≤16: ±0.2 16<L≤63: ±0.3				DRAWN & DRAFTED BY		LIN HUA JING