



備註說明:

1. PART NO. : HX-3037 量产模
 2. MATERIAL: PM-9820 MUST MEET UL94V-0
 3. COLOR: BLACK (黑色)
 4. CORE TYPE: CC-3012
 5. MATERIAL OF PIN : 3/4H CP WIRE, 圆0.80 ± 0.05
 6. DIMENSION MARK : Δ MAIN DIM., \otimes SECOND DIM, OTHER WIRE ARE REFERENTIAL DIM.
 7. 強度要求: 2.00kg MIN
 8. 耐壓要求: 4KV/1.5mA/1分鐘
 9. 焊錫溫度: 450° ± 10° 3SEC
 10. 拉力: 焊後拉力 1.5kg MIN
- 标示的 Δ 为重要尺寸, 标示的 \otimes 为次要尺寸.

客户确认
签回

RoHS
HF

| REV. | REVISION RECORD | DATE | REV | REVISION RECORD | DATE |
|------|-----------------|------|-----|-----------------|------|
| 01 | | | 03 | | |
| 02 | | | 04 | | |

| NAME | CC-3012(5P) | MATERIAL | PM-9820 | SCALE | 1:1 | ANGLE | ±1° |
|--|-------------|---|---------|---|-----|-----------------------------|-----|
| DRAWING NO. | HX 3037 | PIN MATERIAL | CP WIRE | UNIT | m/m | REV. | 00 |
|  东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com | | TOLERANCE OF PIN DIA ±0.05 | |  | | PIN TENSION LOAD 1.0 kg MIN | |
| | | TOLERANCE: 0 < L < 4: ±0.1 4 < L < 16: ±0.2 16 < L < 63: ±0.3 | | UL REC. : 94V0 | | | |
| DRAWN & DRAFTED BY | | LIN HUA JING | | CHECKED & APPROVED BY | | DATE: NOV 25 2014 | |