



備註:

1. 焊錫溫度: 450° ±10° 3SEC
2. 焊錫前拉力: 1.0kgf MIN
3. 焊錫後拉力: 1.50kgf MIN
4. 阻燃測試: 燃燒10SEC, 在10SEC內自然熄滅。
5. 耐壓測試: 4.5KV, 0.5mA, 3SEC
6. 強度: 1.0kgf MIN
7. 量產模

客户确认  
 簽回

RoHS  
 HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01	△ 尺寸0.60改為0.80	2022/09/30	03		
02			04		

NAME	EED-4116 (7P)	MATERIAL	PM-9820	SCALE	1:1	ANGLE	±1°	
DRAWING NO.	HX-4109C	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	01	
东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com		TOLERANCE OF PIN DIA ±0.05				PIN TENSION LOAD kg MIN		UL REC. :94V0
		TOLERANCE: 0<L<4: ±0.1 4<L<16: ±0.2 16<L<63: ±0.3				DRAWN & DRAFTED BY		LIN HUA JING