


PIN咬花外露 (Textured exposed)
DETAIL B (3:1)



備註 (NOTE):

1. 材質 (Material): PM-9820
2. 強度要求 (Strength requirement): 2.80kg MIN
3. 耐壓要求 (HI-POT requirements): 4KV/1.5mA/1min
4. 焊錫溫度 (Soldering temperature): 450° ± 10° 3SEC
5. 拉力 (Pull): 焊後拉力 (After welding tension) 1.53kg MIN
6. 模具狀況 (The mould status): 量產模 (Formal mold)
7. PIN 12, 13 CUT

客户确认
签回

RoHS
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01	0尺寸12.0±0.1改為11.80+0.2/-0.1, BASE寬度7.00改為7.10, 下葉片連接處C角由0.50改為0.80	2016/10/11	03		
02	PIN外露咬花點寬度由1.60改為2.00	2016/12/21	04		

NAME	EER-28S (12+1P)	MATERIAL	PM-9820	SCALE	1:1	ANGLE	±1°
DRAWING NO.	HX-2859	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	02
		TOLERANCE OF PIN DIA ±0.05 PIN TENSION LOAD kg MIN					
东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com		TOLERANCE: 0<L<4: ±0.1 4<L<16: ±0.2 16<L<63: ±0.3		DRAWN & DRAFTED BY LIN HUA JING CHECKED & APPROVED BY DATE: MAY 23 2016			