



備註說明:

1. 材質: T375HF
2. 強度要求: 2.00kg MIN
3. 耐壓要求: 4KV/1.5mA/1分鐘
4. 焊錫溫度: 450° ±10° 3SEC
5. 拉力: 焊後拉力 1.5kg MIN
6. 模具狀況: 量產模

A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P
10.30	20.80	18.00	26.00	12.00	14.70	12.80	3.00	PL	17.50	0.80	12.30	9.50	2.50	25.50	5.00
±0.1	±0.2	±0.2	±0.3	±0.2	±0.2	±0.2	±0.1	±0.2	±0.15	±0.05	±0.2	±0.2	±0.1	±0.3	±0.15

Q	R	S	T	U
3.50	30.00	12.00	26.20	
±0.15	±0.3	±0.2	±0.3	

客户确认				RoHS HF
签回				

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	EER-2825 (14P)	MATERIAL	T375HF	SCALE	1:1	ANGLE	±1°
DRAWING NO.	HX-2863	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	00
		TOLERANCE OF PIN DIA ±0.05					
DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD.		PIN TENSION LOAD 1.0 kg MIN		UL REC. :94V0			
TEL:0769-86388088 86388188 86388288 FAX:0769-86388111		TOLERANCE: 0<L<4: ±0.1 4<L<16: ±0.2 16<L<63: ±0.3					
http://www.hxbobbin.com E-Mail:hxbobbin@vip.163.com		DRAWN & DRAFTED BY	LIN HUA JING	CHECKED & APPROVED BY		DATE:	AUG 18 2017