



PIN 咬花外露 (Textured exposed)  
DETAIL B (3:1)

備註 (NOTE):

1. 材質 (Material): PM-9820
2. 強度要求 (Strength requirement): 2.80kg MIN
3. 耐壓要求 (HI-POT requirements): 4KV/1.5mA/1Min
4. 焊錫溫度 (Soldering temperature): 450° ±10° 3SEC
5. 拉力 (Pull): 焊後拉力 (After welding tension) 1.53kg MIN
6. 模具狀況 (The mould status): 量產模
7. 最小壁厚: 0.90mm

客户确认  
簽回

RoHS  
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	EER-28S (12P)	MATERIAL	PM-9820	SCALE	1:1	ANGLE	±1°
DRAWING NO.	HX-2874A2	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	00
		TOLERANCE OF PIN DIA ±0.05 PIN TENSION LOAD kg MIN		TOLERANCE: 0<L<4: ±0.1    4<L<16: ±0.2    16<L<63: ±0.3		UL REC.: 94V0	
东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com		DRAWN & DRAFTED BY LIN HUA JING	CHECKED & APPROVED BY	DATE:	OCT 14 2022		