


備註說明:

1. 材質: T375HF
2. 強度要求: 1.80kg MIN,
3. 耐壓要求: 4KV/1.5mA/60S
4. 焊錫溫度: 450° ±10° 3SEC
5. 拉力: 焊錫前1.00kg MIN, 焊錫後2.00kg MIN
6. 模具狀況: 量產模
7. PIN來回90° 彎折一次無折斷, 龜裂。



A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S
13.60	15.00	24.80	13.00	5.50	5.00	2.50	10.30	18.30	26.00	20.60	1.50	PL	27.50	0.80	12.70	29.00	21.00	31.00
+0.2 -0.1	±0.2	±0.2	±0.2	±0.2	±0.15	±0.1	±0.2	±0.3	±0.3	±0.3	±0.1	±0.2	±0.2	±0.05	±0.2	±0.3	±0.3	±0.3

客户确认
签回

RoHS
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	EER-3019(10P)	MATERIAL	T375HF	SCALE	1:1	ANGLE	±1°
DRAWING NO.	HX 3009	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	00
东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO.,LTD. TEL:0769-86388088 86388188 86388288 FAX:0769-86388111 http://www.hxbobbin.com E-Mail:hxbobbin@vip.163.com		TOLERANCE OF PIN DIA ±0.05				UL REC. :94V0	
		TOLERANCE: 0<L<4: ±0.1 4<L<16: ±0.2 16<L<63: ±0.3		DRAWN & DRAFTED BY		CHECKED & APPROVED BY	
		LIN HUA JING					