



備註:

1. 焊錫溫度: 450° ±10° 3SEC
2. 焊錫前拉力: 1.0kgf MIN
3. 焊錫後拉力: 1.50kg MIN
4. 阻燃測試: 燃燒10SEC, 在10SEC內自然熄滅。
5. 耐壓測試: 4.5KV, 0.5mA, 3SEC

客户确认
签回

RoHS
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	ER-3124(10P)	MATERIAL	PM-9820	SCALE	1.5:1	ANGLE	±1°
DRAWING NO.	HX 3104	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	00
 东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO.,LTD. TEL:0769-86388088 86388188 86388288 FAX:0769-86388111 http://www.hxbobbin.com E-Mail:hxbobbin@vip.163.com		TOLERANCE OF PIN DIA ±0.05					
		PIN TENSION LOAD 1.5 kg MIN				UL REC. :94V0	
		TOLERANCE: 0<L≤4: ±0.1 4<L≤16: ±0.2 16<L≤63: ±0.3					
DRAWN & DRAFTED BY		LIN HUA JING		CHECKED & APPROVED BY		DATE: MAR 26 2009	