



備註說明:

1. PART NO. : HX-3235A 樣品模
2. MATERIAL: PM-9823 MUST MEET UL94V-0
3. COLOR: BLACK
4. CORE TYPE: ERI-3230
5. MATERIAL OF PIN : 3/4H CP WIRE, $\phi 0.80 \pm 0.05$
6. DIMENSION MARK : \triangle MAIN DIM. , \otimes SECOND DIM, OTHERWIRE ARE REFERENTIAL DIM. .
标示的 \triangle 为重要尺寸, 标示的 \otimes 为次要尺寸.

7. 強度要求: 1.20kg MIN
8. 耐壓要求: 4KV/1.5mA/60S
9. 焊錫溫度: $450^\circ \pm 10^\circ$ 3SEC
10. 拉力: 焊後拉力 1.5kg MIN
11. HX-3235A與HX-3235B裝配OK

客户确认
签回

RoHS
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	ERI-3230(11P)	MATERIAL	PM-9823	SCALE	1/1	ANGLE	$\pm 1^\circ$
DRAWING NO.	HX-3235A	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	00
		TOLERANCE OF PIN DIA ± 0.05				PIN TENSION LOAD kg MIN	
DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO.,LTD. TEL:0769-86388088 86388188 86388288 FAX:0769-86388111 http://www.hxbobbin.com E-Mail:hxbobbin@vip.163.com		TOLERANCE: $0 < L < 4 : \pm 0.1$		$4 < L < 16 : \pm 0.2$		$16 < L < 63 : \pm 0.3$	
DRAWN & DRAFTED BY LIN HUA JING		CHECKED & APPROVED BY		DATE: JAN 13 2016			