



備註說明:

1. 材質: PM-9820
2. 強度要求: 3.00kg MIN
3. 耐壓要求: 4KV/1.5mA/1分鐘
4. 焊錫溫度: 450° ±10° 3SEC
5. 拉力: 焊後拉力 1.53kg MIN
6. 模具狀況: 正式模

客户确认
签回

RoHS
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	ERL-28 (12P)	MATERIAL	PM-9820	SCALE	1.5/1	ANGLE	±1°
DRAWING NO.	HX-2804	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	00


东莞市华欣塑胶制品有限公司
 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD.
 TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111
 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com

TOLERANCE OF PIN DIA	±0.05	
PIN TENSION LOAD	1.5 kg MIN	UL REC. :94V0
TOLERANCE:	0<L<4: ±0.1 4<L<16: ±0.2 16<L<63: ±0.3	
DRAWN & DRAFTED BY	LIN HUA JING	CHECKED & APPROVED BY
DATE:	DEC 16 2003	