



備註說明:

1. 材質: T375HF
2. 強度要求: 2.50kg MIN
3. 耐壓要求: 4KV/1.5mA/1分鐘
4. 焊錫溫度: 450° ± 10° 3SEC
5. 拉力: 焊後拉力 1.53kg MIN
6. 模具狀況: 量产模

客户确认
签回

RoHS
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	ERL-28 (12P)	MATERIAL	T375HF	SCALE	1/1	ANGLE	± 1°
DRAWING NO.	HX 2819	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	00



东莞市华欣塑胶制品有限公司
DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD.
TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111
http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com

TOLERANCE OF PIN DIA	± 0.05	
PIN TENSION LOAD	1.5 kg MIN	UL REC. : 94V0
TOLERANCE:	0 < L < 4 : ± 0.1 4 < L < 16 : ± 0.2 16 < L < 63 : ± 0.3	
DRAWN & DRAFTED BY	LIN HUA JING	CHECKED & APPROVED BY
DATE:	DEC 26 2005	