



**備註 (NOTE):**

1. 材質 (Material): PM-9630
2. 強度要求 (Strength requirement): 6PIN邊BASE強度1.50kg MIN,  
6PIN邊BASE小凸點強度1.0kg MIN,  
其他位置1.50kg MIN
3. 耐壓要求 (HI-POT requirements): 4KV/1.5mA/1Min
4. 焊錫溫度 (Soldering temperature): 450° ±10° 3SEC
5. 拉力 (Pull): 焊後拉力 (After welding tension) 1.50kg MIN
6. 模具狀況 (The mould status): 量產模 (Formal mold)

客户确认  
簽回

**RoHS**  
**HF**

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	LQ-25B (6+4P)	MATERIAL	PM-9630	SCALE	1:1	ANGLE	±1°
DRAWING NO.	HX-2546A	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	00
		TOLERANCE OF PIN DIA ±0.05 PIN TENSION LOAD kg MIN					
东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com		TOLERANCE: 0<L≤4: ±0.1 4<L≤16: ±0.2 16<L≤63: ±0.3		UL REC.: 94V0			
DRAWN & DRAFTED BY		LIN HUA JING		CHECKED & APPROVED BY		DATE: SEP 14 2016	