



備註 (NOTE):

1. 材質 (Material): PM-9630
2. 強度要求 (Strength requirement): 1.00kg MIN
3. 耐壓要求 (HI-POT requirements): 4KV/1.5mA/1Min
4. 焊錫溫度 (Soldering temperature): 450° ±10° 3SEC
5. 拉力 (Pull): 焊後拉力 (After welding tension) 1.50kg MIN
6. 模具狀況 (The mould status): 量產模 (Formal mold)

客户确认
签回

RoHS
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01	缺口兩側直角改為R2.00	2021/02/01	03		
02			04		

NAME	LQ-25B (COVER)	MATERIAL	PM-9630	SCALE	1:1	ANGLE	±1°	
DRAWING NO.	HX-2546B	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	01	
 东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com		TOLERANCE OF PIN DIA ±0.05				PIN TENSION LOAD kg MIN		UL REC. :94V0
		TOLERANCE: 0<L<4: ±0.1 4<L<16: ±0.2 16<L<63: ±0.3				DRAWN & DRAFTED BY		LIN HUA JING