



**備註 (NOTE):**

1. 材質 (Material): PM-9823
2. 強度要求 (Strength requirement): 1.50kg MIN
3. 耐壓要求 (HI-POT requirements): 4KV/1.5mA/1min
4. 焊錫溫度 (Soldering temperature): 450° ±10° 3SEC
5. 模具狀況 (The mould status): 量產模 (Formal mold)

6. 底部焊錫前平貼度 0.10mm MAX  
底部焊錫後平貼度 0.12mm MAX
7. 與 HX-2551A 匹配 OK
8. 包裝前燒烤 180°C 4H, 防止焊錫後起泡

R	S	T
8.50	1.00	2.00
±0.2	±0.1	±0.1

A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q
29.00	23.10	27.20	22.10	2.60	9.40	17.60	30.20	25.60	4.00	0.90	0.50	2.40	13.40	4.00	4.00	2.00
±0.3	±0.3	±0.3	±0.3	±0.1	+0.2 -0.1	+0.2 -0.1	±0.3	+0.2 -0.1	±0.2	±0.1	±0.1	±0.1	±0.2	±0.2	±0.2	±0.1

客户确认  
签回



REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	LQ-25-14.3 (COVER)	MATERIAL	PM-9823	SCALE	1:1	ANGLE	±1°
DRAWING NO.	HX-2551B	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	00
		TOLERANCE OF PIN DIA ±0.05				UL REC. :94V0	
东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO.,LTD. TEL:0769-86388088 86388188 86388288 FAX:0769-86388111 http://www.hxbobbin.com E-Mail:hxbobbin@vip.163.com		TOLERANCE: 0<L<4: ±0.1 4<L<16: ±0.2 16<L<63: ±0.3		DRAWN & DRAFTED BY		DATE: MAY 05 2018	
		LIN HUA JING		CHECKED & APPROVED BY			