

進膠口位置


備註說明:

1. 材質: PM-9630
2. 強度要求:
PIN1-5 BASE強度: 4.50kg MIN
PIN6-9 BASE強度: 4.00kg MIN
3. 耐壓要求: 4KV/1.5mA/1分鐘
4. 焊錫溫度: 450° ±10° 3SEC
5. 焊錫後拉力: 3.50kg MIN (PIN1-5); 1.2kg MIN (PIN10-11)
6. 模具狀況: 量產模

客户确认
簽回

RoHS
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01	△ 直口尺寸2.00改為2.20; 斜口尺寸1.86改為2.20	2022/07/29	03	△ 尺寸3.0改為3.4; 尺寸3.3改為4.35; 尺寸R1.0改為R10.0 尺寸1.8改為2.1	2022/11/18
02	△ J尺寸15.2改為15.55; U尺寸9.2改為9.5; 尺寸1.2改為1.5; 增加C角0.7	2022/10/07	04		

NAME	LRS-3916 (5+2P)	MATERIAL	PM-9630	SCALE	1:1	ANGLE	±1°
DRAWING NO.	HX-3913	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	03
 东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com		TOLERANCE OF PIN DIA ±0.05					
		PIN TENSION LOAD 1.5 kg MIN				UL REC.: 94V0	
		TOLERANCE: 0<L<4: ±0.1 4<L<16: ±0.2 16<L<63: ±0.3					
DRAWN & DRAFTED BY		LIN HUA JING	CHECKED & APPROVED BY		DATE: JUN 01 2022		