



備註說明:

1. 材質: PM-9820
2. 強度要求: 1.50kg MIN
3. 耐壓要求: 4KV/1.5mA/1分鐘
4. 焊錫溫度:  $450^{\circ} \pm 10^{\circ}$  3SEC
5. 拉力: 焊後拉力 1.5kg MIN
6. 模具狀況: 正式模

V	W
19.80	29.40
$\pm 0.2$	$\pm 0.3$

A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U
21.50	14.20	4.40	10.80	3.50	7.60	9.10	25.10	3.80	21.70	14.40	11.70	0.80	1.10	PL	25.40	11.10	0.70	12.50	26.50	12.60
$\pm 0.3$	$\pm 0.2$	$\pm 0.2$	$\pm 0.2$	$\pm 0.1$	$\pm 0.15$	$\pm 0.15$	$\pm 0.3$	$\pm 0.3$	$\pm 0.3$	$\pm 0.15$	$\pm 0.2$	$\pm 0.1$	$\pm 0.1$	$\pm 0.2$	$\pm 0.15$	$^{+0.1}_{-0.2}$	$\pm 0.05$	$\pm 0.2$	$\pm 0.3$	$\pm 0.2$

客户确认  
签回

RoHS  
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01	1. D尺寸由6.30改为6.80, E尺寸由3.00改为3.50, H尺寸由20.60改为21.10	2015/04/07	03		
02	1. R尺寸线径由0.6改为0.70	2015/07/02	04		

NAME	PQ-2620 (12P)	MATERIAL	PM-9820	SCALE	1.5:1	ANGLE	$\pm 1^{\circ}$
DRAWING NO.	HX-2608	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	02
东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com		TOLERANCE OF PIN DIA $\pm 0.05$					
		TOLERANCE: $0 < L \leq 4: \pm 0.1$ $4 < L \leq 16: \pm 0.2$ $16 < L \leq 63: \pm 0.3$			UL REC. :94V0		
DRAWN & DRAFTED BY	LIN HUA JING	CHECKED & APPROVED BY		DATE:	MAR 14 2015		