



備註說明:

1. Mold condition.: HX-2618 正式模
2. MATERIAL: PM-9820 MUST MEET UL94V-0
3. COLOR: BLACK
4. CORE TYPE: PQ-2625
5. MATERIAL OF PIN : 3/4H CP WIRE, $\square 0.70 \pm 0.03$
6. DIMENSION MARK : \triangle MAIN DIM., \otimes SECOND DIM, OTHERWIRE ARE REFERENTIAL DIM..
- 7 标示的 \triangle 为重要尺寸, 标示的 \otimes 为次要尺寸.
7. 強度要求: 1.80kg MIN,
8. 耐壓要求: 4KV/1.5mA/1分鐘
9. 焊錫溫度: $450^\circ \pm 10^\circ$ 3SEC
10. 拉力: 焊後拉力 1.5kg MIN

客户确认
签回

RoHS
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	PQ-2625 (7P)	MATERIAL	PM-9820	SCALE	1:1	ANGLE	$\pm 1^\circ$
DRAWING NO.	HX-2618	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	00



东莞市华欣塑胶制品有限公司
DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD.
TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111
http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com

TOLERANCE OF PIN DIA	± 0.05	
PIN TENSION LOAD	1.5 kg MIN	UL REC.: 94V0
TOLERANCE:	$0 < L < 4: \pm 0.1$ $4 < L < 16: \pm 0.2$ $16 < L < 63: \pm 0.3$	
DRAWN & DRAFTED BY	LIN HUA JING	CHECKED & APPROVED BY
DATE:	SEP 18 2013	