


備註說明:

- PART NO. : HX-2620A 樣品模
- MATERIAL: PM-9820 MUST MEET UL94V-0
- COLOR: BLACK
- CORE TYPE: PQ-2630
- MATERIAL OF PIN : 3/4H CP WIRE,  $\square 0.80 \pm 0.05$
- DIMENSION MARK :  $\triangle$  MAIN DIM.,  $\otimes$  SECOND DIM., OTHERWIRE ARE REFERENTIAL DIM.  
标示的  $\triangle$  为重要尺寸, 标示的  $\otimes$  为次要尺寸。
- 強度要求: 1.80kg MIN
- 耐壓要求: 4KV/1.5mA/1分鐘
- 焊錫溫度:  $450^\circ \pm 10^\circ$  3SEC
- 拉力: 焊後拉力 1.5kg MIN
- HX-2620A與HX-2620B裝配OK



客户确认  
签回

RoHS  
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	PQ-2630 (9P)	MATERIAL	PM-9820	SCALE	1:1	ANGLE	$\pm 1^\circ$
DRAWING NO.	HX-2620A	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	00



东莞市华欣塑胶制品有限公司  
DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD.  
TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111  
http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com

TOLERANCE OF PIN DIA	$\pm 0.05$	
PIN TENSION LOAD	1.5 kg MIN	UL REC. : 94V0
TOLERANCE:	$0 < L < 4 : \pm 0.1$ $4 < L < 16 : \pm 0.2$ $16 < L < 63 : \pm 0.3$	
DRAWN & DRAFTED BY	LIN HUA JING	CHECKED & APPROVED BY
DATE:	DEC 12 2013	