



備註說明:

1. Mold condition.: HX 2621 正式模
2. MATERIAL: PM-9820 MUST MEET UL94V-0
3. COLOR: BLACK
4. CORE TYPE: PQ-2620/2625
5. MATERIAL OF PIN : 3/4H CP WIRE,  $\square 0.80 \pm 0.05$
6. DIMENSION MARK :  $\triangle$  MAIN DIM. ,  $\otimes$  SECOND DIM, OTHERWIRE ARE REFERENTIAL DIM. .  
标示的  $\triangle$  为重要尺寸, 标示的  $\otimes$  为次要尺寸.
7. 強度要求: 1.80kg MIN,
8. 拉力: 焊後拉力 2.00kg MIN
9. 尺寸公差:
  - 0-1  $\pm 0.06$
  - 1-4  $\pm 0.1$
  - 4-16  $\pm 0.15$
  - 16-63  $\pm 0.2$

客户确认		RoHS HF
签回		

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	PQ-26 (12P)	MATERIAL	PM-9820	SCALE	1:1	ANGLE	$\pm 1^\circ$
DRAWING NO.	HX 2621	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	00
东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO.,LTD. TEL:0769-86388088 86388188 86388288 FAX:0769-86388111 http://www.hxbobbin.com E-Mail:hxbobbin@vip.163.com		TOLERANCE OF PIN DIA $\pm 0.05$					
		PIN TENSION LOAD 1.5 kg MIN		UL REC. :94V0			
		TOLERANCE: $0 < L < 4: \pm 0.1$		$4 < L < 16: \pm 0.2$		$16 < L < 63: \pm 0.3$	
DRAWN & DRAFTED BY		LIN HUA JING		CHECKED & APPROVED BY		DATE: JUL 31 2014	