


備註說明:

1. 材質: PM-9823
2. 強度要求: 1.50kg MIN
3. 耐壓要求: 4KV/1.5mA/1分鐘
4. 焊錫溫度: 450° ±10° 3SEC
5. 拉力: 焊後拉力 1.5kg MIN
6. 模具狀況: 正式模



V	W
20.00	29.40
+0.3	±0.3
-0	

A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U
21.50	14.20	4.40	10.50	3.50	7.60	9.10	24.80	3.80	21.70	14.40	11.70	0.80	1.10	PL	25.40	11.10	0.70	12.50	26.50	12.60
±0.3	±0.2	±0.2	±0.2	±0.1	±0.15	±0.15	±0.3	±0.1	±0.3	±0.15	±0.2	±0.1	±0.1	±0.2	±0.15	+0.1 -0.2	±0.05	±0.2	±0.3	±0.2

客户确认
签回



REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01	V尺寸由19.80±0.2改为20.00+0.3/-0	2016/04/26	03		
02			04		

NAME	PQ-2620 (12P)	MATERIAL	PM-9823	SCALE	1:1	ANGLE	±1°
DRAWING NO.	HX-2625	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	01
		TOLERANCE OF PIN DIA ±0.05 PIN TENSION LOAD 1.0 kg MIN					
东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com		TOLERANCE: 0<L<4: ±0.1 4<L<16: ±0.2 16<L<63: ±0.3		UL REC.: :94V0			
DRAWN & DRAFTED BY	LIN HUA JING	CHECKED & APPROVED BY		DATE:	DEC 07 2015		