



PIN需咬花外露




備註說明:

1. 材質: PM-9630
2. 耐壓要求: 4KV/1.5mA/1分鐘
3. 焊錫溫度: 450° ±10° 3SEC
4. 強度要求: 2.0kg MIN
5. 拉力: 焊前是1.0kg MIN, 焊後是1.5kg MIN
6. 模具狀況: 量產模

客户确认
签回

RoHS
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	PQ-26 (4P)	MATERIAL	PM-9630	SCALE	1:1	ANGLE	±1°
DRAWING NO.	HX 2632	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	00
 东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com		TOLERANCE OF PIN DIA ±0.05 PIN TENSION LOAD kg MIN		 UL REC.: 94V0			
		TOLERANCE: 0<L<4: ±0.1 4<L<16: ±0.2 16<L<63: ±0.3					
DRAWN & DRAFTED BY		LIN HUA JING		CHECKED & APPROVED BY		DATE: JUN 26 2021	