



備註說明:

1. 材質: PM-9823
2. 強度要求: 1.50kg MIN
3. 耐壓要求: 4KV/1.5mA/1分鐘
4. 焊錫溫度: 450° ±10° 3SEC
5. 拉力: 焊後拉力 1.5kg MIN
6. 模具狀況: 量產模

客户确认  
签回

RoHS  
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	PQ-32 (4P)	MATERIAL	PM-9823	SCALE	1:1	ANGLE	±1°
DRAWING NO.	HX-3209	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	00
 <p>东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com</p>	TOLERANCE OF PIN DIA ±0.05		— ⊕ —				
	PIN TENSION LOAD 1.5 kg MIN		UL REC. :94V0				
	TOLERANCE: 0<L<4: ±0.1 4<L<16: ±0.2 16<L<63: ±0.3						
DRAWN & DRAFTED BY	LIN HUA JING	CHECKED & APPROVED BY		DATE:	MAR 23 2010		