



備註說明:

1. PART NO. : HX-3227A 量產模
2. MATERIAL: PM-9820 MUST MEET UL94V-0
3. COLOR: BLACK
4. CORE TYPE: PQ-3230
5. MATERIAL OF PIN : 3/4H CP WIRE, $\square 0.80 \pm 0.05$
6. DIMENSION MARK : \triangle MAIN DIM., \otimes SECOND DIM., OTHERWISE ARE REFERENTIAL DIM.
- 標示的 \triangle 为重要尺寸, 标示的 \otimes 为次要尺寸。
7. 強度要求: 1.80kg MIN
8. 耐壓要求: 4KV/1.5mA/1分鐘
9. 焊錫溫度: $450^\circ \pm 10^\circ$ 3SEC
10. 拉力: 焊後拉力 1.5kg MIN
11. HX-3227A與HX-3227B裝配OK

客户确认
签回

RoHS
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01			03		
02			04		

NAME	PQ-3230 (9P)	MATERIAL	PM-9820	SCALE	1:1	ANGLE	$\pm 1^\circ$
DRAWING NO.	HX-3227A	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	00
		TOLERANCE OF PIN DIA ± 0.05 PIN TENSION LOAD kg MIN				UL REC. : 94V0	
东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO.,LTD. TEL:0769-86388088 86388188 86388288 FAX:0769-86388111 http://www.hxbobbin.com E-Mail:hxbobbin@vip.163.com		TOLERANCE: $0 < L < 4: \pm 0.1$ $4 < L < 16: \pm 0.2$ $16 < L < 63: \pm 0.3$		DRAWN & DRAFTED BY LIN HUA JING		CHECKED & APPROVED BY	
				DATE: NOV 12 2013			