



備註說明:

1. 材質: PET-FR530(BK)
2. 強度要求: 葉片強度1.50kg MIN
其他部位強度2.00kg MIN
3. 耐壓要求: 4KV/1.5mA/1分鐘
4. 焊錫溫度: 380° ±10° 3SEC
5. 模具狀況: 量產模

RoHS

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
A			C		
B			D		

NAME	PQ-3218	MATERIAL	PET-FR530	SCALE	1/1	ANGLE	±1°
DRAWING NO.	HX-3230	PIN MATERIAL		UNIT	m/m	REV.	00



东莞市华欣塑胶制品有限公司
DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO.,LTD.
TEL:0769-86388088 86388188 86388288 FAX:0769-86388111
http://www.hxbobbin.com E-Mail:hxbobbin@vip.163.com

TOLERANCE OF PIN DIA ±0.05		— ⊕ —	
PIN TENSION LOAD kg MIN		UL REC. :94V0	
TOLERANCE: 0<L<4: ±0.1 4<L<16: ±0.2 16<L<63: ±0.3			
DRAWN & DRAFTED BY	LIN HUA JING	CHECKED & APPROVED BY	LIN GUO PING
DATE:		AUG 14 2015	