



備註說明:

1. PART NO.: HX3815 量產模
2. MATERIAL: PM-9820 MUST MEET UL94V-0
3. COLOR: BLACK
4. CORE TYPE: PQ-3820
5. MATERIAL OF PIN : 3/4H CP WIRE, SQ0.80 ± 0.05
6. DIMENSION MARK : Δ MAIN DIM., \otimes SECOND DIM, OTHERWIRE ARE REFERENTIAL DIM.
标示的 Δ 为重要尺寸, 标示的 \otimes 为次要尺寸.
7. 強度要求: 1.80kg MIN
8. 耐壓要求: 4KV/1.5mA/1分鐘
9. 焊錫溫度: 450° ± 10° 3SEC
10. 拉力: 焊後拉力 1.5kg MIN

客户确认
签回

RoHS
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01	1. F尺寸 16.00 ± 0.2 改為 16.00 ± 0.3 / -0	2014/08/20	03		
02			04		

NAME	PQ-3820 (14P)	MATERIAL	PM-9820	SCALE	1:1	ANGLE	± 1°
DRAWING NO.	HX 3815	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	01
<p>东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com</p>		TOLERANCE OF PIN DIA ± 0.05				PIN TENSION LOAD 1.5 kg MIN	
		TOLERANCE: 0 < L < 4: ± 0.1 4 < L < 16: ± 0.2 16 < L < 63: ± 0.3				UL REC.: 94V0	
DRAWN & DRAFTED BY	LIN HUA JING	CHECKED & APPROVED BY		DATE:	MAR 04 2014		