



Notes:

- 1. Max permissible flashes are 0.1mm.
 - 2. Max flashes in winding area are 0.05mm.
- Pin tension load: 1.5Kg Min

客户确认
签回

RoHS
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01	頂部增加防呆點識別	2021/05/11	03		
02			04		

NAME	PQ-3816 (4P)	MATERIAL	PF-2736	SCALE	1:1	ANGLE	±1°
DRAWING NO.	HX 3818	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	01
<p>东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com</p>		TOLERANCE OF PIN DIA ±0.05				UL REC. :94V0	
		PIN TENSION LOAD 1.5 kg MIN		TOLERANCE: 0<L≤4: ±0.1 4<L≤16: ±0.2 16<L≤63: ±0.3			
DRAWN & DRAFTED BY		LIN HUA JING		CHECKED & APPROVED BY		DATE: NOV 11 2014	