



備註說明:

- PART NO.: HX-2301C 量產模
- MATERIAL: PET-FR530 MUST MEET UL94V-0
- COLOR: NC
- CORE TYPE: SQ-2318
- DIMENSION MARK: \triangle MAIN DIM., \otimes SECOND DIM., OTHERWISE ARE REFERENTIAL DIM.
标示的 \triangle 重要尺寸, 标示的 \otimes 为次要尺寸。
- 強度要求: 中間葉片1.00kg MIN, 其他部位2.00kg MIN.

- 耐壓要求: 4KV/1.5mA/1分鐘
- 焊錫溫度: 450° ±10° 3SEC
- HX-2301C與HX-2301A匹配OK

RoHS

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
A			C		
B			D		

NAME	SQ-2318 GEAR	MATERIAL	PET-FR530	SCALE	2:1	ANGLE	±1°	
DRAWING NO.	HX-2301C	PIN MATERIAL		UNIT	m/m	REV.	00	
<p>东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com</p>		TOLERANCE OF PIN DIA ±0.05				PIN TENSION LOAD kg MIN		UL REC.: 94V0
		TOLERANCE: 0<L<4: ±0.1 4<L<16: ±0.2 16<L<63: ±0.3				DRAWN & DRAFTED BY		LIN HUA JING