



備註說明:

1. 材質: PF-2736
2. 強度要求: 2.50kg MIN
3. 耐壓要求: 4KV/1.5mA/1分鐘
4. 焊錫溫度: 450° ±10° 3SEC
5. 拉力: 焊後拉力 1.5kg MIN
6. 模具狀況: 正式模

紅色線條位置是合模線

進膠口位置

A	B	C	D	E	F	G	H	I	J	K	L	M	N
30.00	26.00	23.30	18.52	21.50	8.00	0.80	PL	14.25	2.50	3.50	3.50	26.80	12.50
±0.3	±0.3	+0.3/-0	+0.3/-0	±0.3	±0.2	±0.05	±0.2	±0.2	±0.1	±0.1	±0.1	±0.2	±0.2

客户确认
签回

RoHS
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01	△ 尺寸22.00改為23.50; 尺寸20.50改為22.00	2019/08/10	03		
02			04		

NAME	SQ-2318 (4P)	MATERIAL	PF-2736	SCALE	1:1	ANGLE	±1°
DRAWING NO.	HX 2314	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	01
东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com		TOLERANCE OF PIN DIA ±0.05				UL REC. :94V0	
		TOLERANCE: 0<L≤4: ±0.1 4<L≤16: ±0.2 16<L≤63: ±0.3		DRAWN & DRAFTED BY		CHECKED & APPROVED BY	
		LIN HUA JING					