



備註說明:

1. 材質: PM-9823
2. 強度要求: 1.8kg MIN
3. 耐壓要求: 4KV/1.5mA/1分鐘
4. 焊錫溫度: 450° ±10° 3SEC
5. 焊後拉力: 1.5kgf MIN
6. 模具狀況: 量產模

客户确认  
签回

RoHS  
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01	增加C角1.80, 分辦PIN脚数法。	2024/06/07	03		
02			04		

NAME	UU-2920 (8P)	MATERIAL	PM-9823	SCALE	1:1	ANGLE	±1°
DRAWING NO.	HX-2906	PIN MATERIAL		UNIT	m/m	REV.	01


**东莞市华欣塑胶制品有限公司**  
 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD.  
 TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111  
 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com

TOLERANCE OF PIN DIA	±0.05	
PIN TENSION LOAD	kg MIN	UL REC. :94V0
TOLERANCE:	0<L≤4: ±0.1    4<L≤16: ±0.2    16<L≤63: ±0.3	
DRAWN & DRAFTED BY	LIN HUA JING	CHECKED & APPROVED BY
DATE:	MAR 14 2025	