



備註說明:

1. 材質: PM-9820
2. 強度要求: 2.00kg MIN
3. 耐壓要求: 4KV/1.5mA/1分鐘
4. 焊錫溫度: 450° ±10° 3SEC
5. 拉力: 焊後拉力 1.53kg MIN
6. 模具狀況: 正式模
7. 標示的  $\triangle$  為重要尺寸, 標示的  $\otimes$  為次要尺寸。

A	B	C	D	E	F	G	H	I	J	K	L
17.20	15.55	14.30	10.20	11.80	1.60	4.10	9.00	7.00	2.50	0.60	4.30
±0.3	±0.2	±0.1	+0.1/-0.15	±0.2	±0.1	±0.3	+0/-0.15	±0.2	±0.1	±0.05	±0.2

M	N	O	P	Q
3.30	4.40	5.40	11.30	14.20
±0.1	±0.1	±0.2	±0.2	±0.2
客户确认 簽回			RoHS HF	

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01	BASE過線槽邊上R角由0.20改為0.50	2016/06/28	03		
02			04		

NAME	WU-2615 (4P)	MATERIAL	PM-9820	SCALE	1:1	ANGLE	±1°
DRAWING NO.	HX-2622	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	01



东莞市华欣塑胶制品有限公司  
DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD.  
TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111  
http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com

TOLERANCE OF PIN DIA	±0.05	
PIN TENSION LOAD	1.5 kg MIN	UL REC. : 94V0
TOLERANCE:	0<L≤4: ±0.1    4<L≤16: ±0.2    16<L≤63: ±0.3	
DRAWN & DRAFTED BY	LIN HUA JING	CHECKED & APPROVED BY
DATE:	NOV 08 2014	