


RoHS

|      |                 |      |     |                 |      |
|------|-----------------|------|-----|-----------------|------|
| REV. | REVISION RECORD | DATE | REV | REVISION RECORD | DATE |
| A    |                 |      | C   |                 |      |
| B    |                 |      | D   |                 |      |

|  |                   |                                   |          |   |                         |                         |               |                   |
|--|-------------------|-----------------------------------|----------|---|-------------------------|-------------------------|---------------|-------------------|
| NAME   | OR $\phi 19$ BASE | MATERIAL                          | PBT-4130 | SCALE   | 2:1                     | ANGLE                   | $\pm 1^\circ$ |                   |
| DRAWING NO.  | HX C010B          | PIN MATERIAL                      |          | UNIT  | m/m                     | REV.                    | 00            |                   |
|  <b>东莞市华欣塑胶制品有限公司</b><br>DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD.<br>TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111<br>http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com |                   | TOLERANCE OF PIN PITCH $\pm 0.05$ |          |  |                         | PIN TENSION LOAD kg MIN |               | UL REC. : 94V0    |
|  |                   | TOLERANCE: $0 < L < 4 : \pm 0.1$  |          | $4 < L < 16 : \pm 0.2$  | $16 < L < 63 : \pm 0.3$ |                         |               |                   |
| DRAWN & DRAFTED BY   |                   | LIN HUA JING                      |          | CHECKED & APPROVED BY   |                         | LIN GUO PING            |               | DATE: MAY 04 2009 |