


備註說明:

1. 材質: LCP-E4008
2. 強度要求: 1.50kg MIN
3. 耐壓要求: 4KV/1.5mA/1分鐘
4. 焊錫溫度: 450° ±10° 3SEC
5. PIN截斷面不可有氧化及露銅現象
6. 包裝方式用吸塑盤裝
7. 模具狀況: 正式模



A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S
3.50	2.70	5.20	6.40	8.50	3.30	2.50	0.70	3.60	9.30	11.00	5.20	5.40	11.00	13.20	4.80	0.30	14.80	12.50
±0.1	±0.1	±0.1	±0.2	±0.2	±0.1	±0.05	±0.1	±0.1	±0.2	±0.2	±0.1	±0.2	±0.2	±0.2	+0.05/-0.1	±0.1	±0.2	±0.1

客户确认
签回

RoHS
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01	R尺寸由14.50改為14.80	2016/01/20	03		
02	C尺寸由5.40±0.1改為5.20±0.1, L尺寸5.50改為5.20±0.1, M尺寸6.00改為5.40	2019/09/18	04		

NAME	S-EI12.5(10P)	MATERIAL	LCP-E4008	SCALE	2:1	ANGLE	±1°
DRAWING NO.	HX S1201	PIN MATERIAL	PHOSPHOR BRONZE	UNIT	m/m	REV.	01
东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com		TOLERANCE OF PIN DIA ±0.05				PIN TENSION LOAD kg MIN	
		TOLERANCE: 0<L<4: ±0.1 4<L<16: ±0.2 16<L<63: ±0.3		UL REC.: 94V0			
DRAWN & DRAFTED BY		LIN HUA JING		CHECKED & APPROVED BY		DATE: MAR 19 2005	