



備註說明:

SEC. A-A



1. 材質: PM-9823
2. 強度要求: 1. 30kg MIN
3. 耐壓要求: 4KV/1. 5mA/1分鐘
4. 焊錫溫度: 450° ±10° 3SEC
5. 拉力: 焊後拉力 1. 02kg MIN
6. 模具狀況: 正式模



A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U
5.60	1.00	2.00	5.00	0.70	8.80	5.70	4.75	1.10	PL	6.80	0.50	2.70	0.50	8.00	8.80	5.10	4.10	8.10	2.30	3.40
±0.1	±0.1	±0.1	±0.2	+0.1 -0	±0.2	+0.05 -0.1	+0.2 -0	±0.1	±0.2	±0.2	±0.05	±0.1	±0.1	±0.2	±0.2	+0 -0.1	+0.1 -0	±0.2	+0.1 -0.05	+0 -0.1

客户确认

签回

RoHS  
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01	1. 中間葉片4個角的R角R0. 3改為R1. 5	2014/07/04	03		
02			04		

NAME	EE-8. 3(4P)	MATERIAL	PM-9823	SCALE	3:1	ANGLE	±1°
DRAWING NO.	HX 0802	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	01
		TOLERANCE OF PIN DIA ±0.05 PIN TENSION LOAD 0.8 kg MIN					
东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com		TOLERANCE: 0<L≤4: ±0.1 4<L≤16: ±0.2 16<L≤63: ±0.3		UL REC. :94V0			
DRAWN & DRAFTED BY		LIN HUA JING		CHECKED & APPROVED BY		DATE: MAY 31 2010	