



備註說明:

1. 材質: PM-9630
2. 強度要求: 1.30kg MIN
3. 耐壓要求: 4KV/1.5mA/1分鐘
4. 焊錫溫度: 450° ±10° 3SEC
5. 拉力: 焊前拉力 1.2kg MIN, 焊後拉力 1.5kg MIN
6. 模具狀況: 正式模

客户确认
签回

RoHS
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01	1. 頂部防呆點加大	2013/10/10	03	1. E尺寸3.90+0.1/-0.05改為3.90+0.2/-0	2015/07/08
02	1. N尺寸8.00改為8.40, R尺寸9.00改為9.40	2014/02/13	04		

NAME	EE-8.3(4P)	MATERIAL	PM-9630	SCALE	3/1	ANGLE	±1°
DRAWING NO.	HX-0818	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	03
		TOLERANCE OF PIN DIA ±0.05 PIN TENSION LOAD 1.2 kg MIN					
东莞市华欣塑胶制品有限公司 DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD. TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111 http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com		TOLERANCE: 0<L≤4: ±0.1 4<L≤16: ±0.2 16<L≤63: ±0.3		UL REC.: 94V0			
DRAWN & DRAFTED BY		LIN HUA JING		CHECKED & APPROVED BY		DATE: JUL 23 2013	