



備註說明:

1. 材質: PM-9823
2. U型PIN: 材質C1100, $\varnothing 1.40 \pm 0.05$
3. 耐壓要求: 任意位置 2.0KV/5mA/3S
4. 焊錫溫度: $440^\circ \pm 10^\circ$ 3SEC
5. 拉力: 焊前 0.8kg MIN, 焊後 1.2g MIN
6. 模具狀況: 量產模

客户确认
签回

RoHS
HF

REV.	REVISION RECORD	DATE	REV	REVISION RECORD	DATE
01	I尺寸同8.20改為8.40±0.2	2019/07/10	03		
02			04		

NAME	EE-10.2 (4P)	MATERIAL	PM-9823	SCALE	1:1	ANGLE	$\pm 1^\circ$
DRAWING NO.	HX-1043	PIN MATERIAL	CP WIRE	UNIT	m/m	REV.	01



东莞市华欣塑胶制品有限公司
DONGGUAN HUAXIN PLASTIC MANUFACTURING PRODUCTS CO., LTD.
TEL: 0769-86388088 86388188 86388288 FAX: 0769-86388111
http://www.hxbobbin.com E-Mail: hxbobbin@vip.163.com

TOLERANCE OF PIN DIA	± 0.05	
PIN TENSION LOAD	kg MIN	UL REC. : 94V0
TOLERANCE:	$0 < L < 4: \pm 0.1$ $4 < L < 16: \pm 0.2$ $16 < L < 63: \pm 0.3$	
DRAWN & DRAFTED BY	LIN HUA JING	CHECKED & APPROVED BY
DATE:	FEB 23 2019	